

SD5600T Thunderbolt™ 3 and USB-C Dual 4K Hybrid Docking Station - 100W PD — Win/Mac

Part Number: K34009US/NA/EU/AP | UPC Code: 8589634009

The ultimate docking station for maximum productivity and compatibility.

Features include universal compatibility, ideal for hot-desking and mixed deployment environments; the flexibility to select between HDMI 2.0 and DP 1.2; 100W of power delivery (perfect for the newer MacBook Pro); horizontal or vertical placement options*; seven USB ports (two with charging), one Gigabit Ethernet port, and one audio combo jack; built-in SD and Micro SD card readers (UHS-II SD 4.0 for the fastest speeds possible); and a three-year warranty. For a zero-footprint mounting option, see our Docking Station Mounting Bracket (K34050WW), sold separately.

Features include:

- True universal compatibility
- 15-port universal docking station
- Support for Thunderbolt 3 and USB-C laptops
- Up to Single or Dual 4K @ 60Hz for Thunderbolt 3 devices
- Flexibility to select between HDMI 2.0 and DP 1.2
- 100W of power delivery

- Data transfer speeds up to 40Gbps (up to 10Gbps for USB-C devices)
- Horizontal or vertical support
- Built-in SD and Micro SD card readers
- Seven USB ports (two with charging), plus one Gigabit Ethernet port, and one audio combo jack
- Free DockWorks™ software
- Three-year warranty



All specifications are subject to change without notice. Products may not be available in all markets. Kensington and the ACCO name and design are registered trademarks of ACCO Brands. Kensington The Professionals' Choice is a trademark of ACCO Brands. All other registered and unregistered trademarks are the property of their respective owners. © 2020 Kensington Computer Products Group, a division of ACCO Brands. All rights reserved. k20-9057p



The Professionals' Choice™

Kensington

SD5600T Thunderbolt™ 3 and USB-C Dual 4K Hybrid Docking Station - 100W PD — Win/Mac

Part Number: K34009US/NA/EU/AP | UPC Code: 8589634009



Universal Compatibility

Perfect for hot-desking and mixed deployment environments, the SD5600T works with Thunderbolt 3 and USB-C laptops running Windows or macOS.



THUNDERBOLT...

Thunderbolt 3 Technology

Allows you to transfer up to 40Gbps of data, video, and audio (10Gbps for USB-C Gen2 laptops, 5Gbps for USB-C Gen1 laptops) using the included Thunderbolt 3 cable, for a quick and powerful plug and play experience.



Single 4K or Dual 4K Video Output for Thunderbolt 3 Enabled Devices*

Extend visual productivity with the crisp resolution, contrast, and color depth of Ultra HD (Single or Dual 4K @ 60Hz) via two DisplayPort ports. USB-C laptops must support Alt Mode.

*For USB-C Alt Mode devices, a maximum resolution of Single 4K 60Hz or Dual 1440p @ 30Hz is supported for HBR3 laptops or Single 4K 30Hz or Dual 1080p @ 60Hz is supported for HBR2 laptops (dual monitors are for devices that support MST).



100W Power Delivery

Quickly and simply charge any Thunderbolt 3 or USB-C enabled laptop. USB-C laptops must support Power Delivery. Ideal for devices that require higher power, such as the newer MacBook Pro.



Productive Desktop Setup

This 15-port universal docking station provides plenty of ports for all your needs: One front USB-C Gen2 port (up to 10Gbps with 5V/1.5A charging), six USB-A ports (1 front Gen2@10Gbps front with 5V/1.5A charging, 5 rear Gen1@5Gbps, 5V/0.9A), one Gigabit Ethernet port, and one audio combo jack.



Flexible Mounting Options

Choose a horizontal or vertical placement on the desktop, or try our optional zero footprint mounting solution (K34050WW).



Built-in SD and Micro SD Card Readers

UHS II SD 4.0 card readers enable ultra-fast file transfer.

Kensington

SD5600T Thunderbolt™ 3 and USB-C Dual 4K Hybrid Docking Station - 100W PD — Win/Mac

Part Number: K34009US/NA/EU/AP | UPC Code: 8589634009

System Requirements	
	System

	Systems Supported	All laptops with Thunderbolt 3 or USB-C ports	
	Operating Systems Supported	Windows® 10, MacOS 10.15+	
	Plug & Play	Yes	
	Software	For Thunderbolt mode in a Windows laptop, please make sure the Intel Thunderbolt software is installed and set to turn on	
	System Resource Requirement	CPU: Intel® Core™ i5 6th Generation or above Memory: 8GB or above GPU: Intel® HD Graphics 620 or above	
	Additional Software Information	DockWorks (Windows 10, macOS 10.15+)	
	USB-C Power Delivery	5V/ 9V/ 12V/ 15V/ 20V @ 3A (up to 100W, 20V @ 5A)	
USB Interface			
	Type of USB Connector	USB-C Connector	
	Host Connector	Supports Thunderbolt 3 or USB Type-C	
USB Connections			
	Front	1 x USB3.1 Gen2 Type A, support BC1.2 (5V/1.5A) 1 x USB3.1 Gen2 Type C (5V/1.5A) 1 x Standard SD slot / 1 x Micro SD slot (SD4.0, UHS-II)	
	Back	5 x USB3.1 Gen1 Type A (5V/0.9A)	
Network Connections			
	Ethernet Port	RJ45	
	Compatible Ethernet Speeds	10/100/1000 Mbps	
Host Connectivity			
	Host Docking Connector	Thunderbolt upstream port with Power Delivery up to 100W	
Video Connections			
	Video Connectors	2 x DisplayPort v1.2 2 x HDMI v2.0	
	Maximum Resolution Supported	TB3 mode: Single Monitor: 4K@ 60Hz Dual Monitors: 4K@ 60Hz	
		USB-C Alt mode: Single Monitor: 4K@ 30Hz (HBR2) Single Monitor: 4K@ 60Hz (HBR3) Dual Monitors: 1080p @ 60Hz (HBR2) Dual Monitors: 1440p @ 60Hz (HBR3)	
Audio Connections			
	Audio Connectors	1 x 3.5mm audio combo jack	
	Audio Channels Supported	Stereo LR	

Kensington

	Enclosure	Aluminum Anodizing Fir	ne Brushed
	Finish	Aluminum Anodizing Fine Brushed PC+ABS	
	Bottom	Metal Base Plate: Sheetmetal	
	Product Color	Silver, Black	
Other Features	Trouder color	Silver, Black	
	Karasin at an Canarita Clat		L / NI= = - Cl = L
	Kensington Security Slot	Kensington Security Slot / Nano Slot	
	VESA Mount Compatible	Yes	
Product Dimensions			
	Unit Dimensions (without peripherals)	Horizontal:	Width: 7.76in (197mm) Depth: 4.09in (104mm) Height: 1.45in (36.8 mm)
		Vertical (with stand):	Width: 2.88in (73.2mm) Depth: 5.56in (141.2mm) Height : 7.98in (202.8mm)
	Unit Weight	1.84lbs (0.835kg)	
	Desktop Footprint	31.67in² (205cm²)	
Packaging Dimensions			
	Packaging Style	Bulk Package (K34009NA/EU) Retail Package (K34009US/AP/JP)	
	Packaging Dimensions	Width: 9.96in (253mm) Depth: 5.98in (152mm) Height: 3.58in (91mm)	
	Packaging Weight	3.84lbs (1.743kg)	
	Packaging Content	SD5600T Dock, TB3 cable, Dock Stand, Power Supply, IG (Instruction Guide), Warranty Card, Compliance Sheet, Welcome card insert for NA/EU SKU	
	Master Carton	4pcs	
Power and Environmer	tal		
	Power Adapter Rating	Input: 100-240V; 1.8A / Output: 20V DC 8.5A (170W)	
	Relative Humidity	55% operating temperature @ 77°F (25°C)	
	Operating Temperature	32 to 104°F (0 to 40°C)	
	Storage Temperature	-0.4 to 140°F (-18 to 60°	C)
Country of Origin, Regu	llatory, and Warranty		
	Country of Origin	Thailand	
	Certification & Compliance	FCC, IC, CE, RCM, VCCI, C	B, RoHS, ACCO RSL
	Warranty	3-Year Limited – Worldw	vide



