

SD5600T Thunderbolt™ 3 and USB-C Dual 4K Hybrid Docking Station - 96W PD — Win/Mac

Part Number: K34009US/NA/EU/AP | UPC Code: 0 85896 34009 6

The ultimate docking station for maximum productivity and compatibility.

Features include universal compatibility, ideal for hot-desking and mixed deployment environments; the flexibility to select between HDMI 2.0 and DP 1.2; 96W of power delivery (perfect for the newer MacBook Pro); horizontal or vertical placement options*; seven USB ports (two with charging), one Gigabit Ethernet port, and one audio combo jack; built-in SD and Micro SD card readers (UHS-II SD 4.0 for the fastest speeds possible); and a three-year warranty. For a zero-footprint mounting option, see our Docking Station Mounting Bracket (K34050WW), sold separately.

Features include:

- True universal compatibility
- 15-port universal docking station
- Support for Thunderbolt 3 and USB-C laptops
- Up to Single or Dual 4K @ 60Hz for Thunderbolt 3 devices
- Flexibility to select between HDMI 2.0 and DP 1.2
- · 96W of power delivery

- Data transfer speeds up to 40Gbps (up to 10Gbps for USB-C devices)
- Horizontal or vertical support
- Built-in SD and Micro SD card readers
- Seven USB ports (two with charging), plus one Gigabit Ethernet port, and one audio combo jack
- Free DockWorks[™] software
- Three-year warranty



All specifications are subject to change without notice. Products may not be available in all markets. Kensington and the ACCO name and design are registered trademarks of ACCO Brands. Kensington The Professionals' Choice is a trademark of ACCO Brands. All other registered and unregistered trademarks are the property of their respective owners. © 2020 Kensington Computer Products Group, a division of ACCO Brands. All rights reserved. k20-9057p



The Professionals' Choice™

Kensington

SD5600T Thunderbolt™ 3 and USB-C Dual 4K Hybrid Docking Station - 96W PD — Win/Mac

Part Number: K34009US/NA/EU/AP | UPC Code: 0 85896 34009 6



Universal Compatibility

Perfect for hot-desking and mixed deployment environments, the SD5600T works with Thunderbolt 3 and USB-C laptops running Windows or macOS.



THUNDERBOLT...

Thunderbolt 3 Technology

Allows you to transfer up to 40Gbps of data, video, and audio (10Gbps for USB-C 3.2 Gen2 laptops, 5Gbps for USB-C Gen1 laptops) using the included 0.8m (2.6 ft.) Thunderbolt 3 cable, for a quick and powerful plug and play experience.



Single 4K or Dual 4K Video Output for Thunderbolt 3 Enabled Devices*

Extend visual productivity with the crisp resolution, contrast, and color depth of Ultra HD (Single or Dual 4K @ 60Hz) via two DisplayPort ports. USB-C laptops must support Alt Mode.

*For USB-C Alt Mode devices, a maximum resolution of Single 4K 60Hz or Dual 1440p @ 60Hz is supported for HBR3 laptops or Single 4K 30Hz or Dual 1080p @ 60Hz is supported for HBR2 laptops (dual monitors are for devices that support MST).



96W Power Delivery

Quickly and simply charge any Thunderbolt 3 or USB-C enabled laptop. USB-C laptops must support Power Delivery. Ideal for devices that require higher power, such as the newer MacBook Pro.



Productive Desktop Setup

This 15-port universal docking station provides plenty of ports for all your needs: One front USB-C 3.2 Gen2 port (up to 10Gbps with 5V/1.5A charging), six USB-A 3.2 ports (1 front Gen2@10Gbps front with 5V/1.5A charging, 5 rear Gen1@5Gbps, 5V/0.9A), one Gigabit Ethernet port, and one audio combo jack.



Flexible Mounting Options

Choose a horizontal or vertical placement on the desktop, or try our optional zero footprint mounting solution (K34050WW).



Built-in SD and Micro SD Card Readers

UHS II SD 4.0 card readers enable ultra-fast file transfer.

Kensington

SD5600T Thunderbolt™ 3 and USB-C Dual 4K Hybrid Docking Station - 96W PD — Win/Mac

Part Number: K34009US/NA/EU/AP | UPC Code: 0 85896 34009 6

System		

System Requirements				
	Systems Supported	All laptops with Thunderbolt 3 or USB-C ports		
	Operating Systems Supported	Windows® 10, MacOS 10.15+		
	Plug & Play	Yes		
	Software	For Thunderbolt mode in a Windows laptop, please make sure the Intel Thunderbolt software is installed and set to turn on		
	System Resource Requirement	CPU: Intel® Core™ i5 6th Generation or above Memory: 8GB or above GPU: Intel® HD Graphics 620 or above		
	Additional Software Information	DockWorks (Windows 10, macOS 10.15+)		
	USB-C Power Delivery	5V/ 9V/ 12V/ 15V/ 20V @ 3A (up to 96W, 20V @ 5A)		
USB Interface				
	Type of USB Connector	USB-C 3.2 Gen2 Connector		
	Host Connector	Supports Thunderbolt 3 or USB Type-C		
USB Connections				
	Front	1 x USB-A 3.2 Gen2, support BC1.2 (5V/1.5A) 1 x USB-C 3.2 Gen2 (5V/1.5A) 1 x Standard SD slot / 1 x Micro SD slot (SD4.0, UHS-II)		
	Back	5 x USB-A 3.2 Gen1 (5V/0.9A)		
Network Connections				
	Ethernet Port	RJ45		
	Compatible Ethernet Speeds	10/100/1000 Mbps		
Host Connectivity				
	Host Docking Connector	Thunderbolt upstream port with Power Delivery up to 96W		
Video Connections				
	Video Connectors	2 x DisplayPort v1.2 2 x HDMI v2.0		
	Maximum Resolution Supported	TB3 mode: Single Monitor: 4K@ 60Hz Dual Monitors: 4K@ 60Hz		
		USB-C Alt mode: Single Monitor: 4K@ 30Hz (HBR2) Single Monitor: 4K@ 60Hz (HBR3) Dual Monitors: 1080p @ 60Hz (HBR2) Dual Monitors: 1440p @ 60Hz (HBR3)		
Audio Connections				
	Audio Connectors	1 x 3.5mm audio combo jack		
	Audio Channels Supported	Stereo LR		

Kensington

	Enclosure	Aluminum Anodizing Fir	ne Brushed	
	Finish	Aluminum Anodizing Fine Brushed PC+ABS		
	Bottom	Metal Base Plate: Sheetmetal		
	Product Color	Silver, Black		
Other Features	Trouder color	Silver, Black		
	Karasin at an Canarita Clat		L / NI= = - Cl = L	
	Kensington Security Slot	Kensington Security Slot / Nano Slot		
	VESA Mount Compatible	Yes		
Product Dimensions				
	Unit Dimensions (without peripherals)	Horizontal:	Width: 7.76in (197mm) Depth: 4.09in (104mm) Height: 1.45in (36.8 mm)	
		Vertical (with stand):	Width: 2.88in (73.2mm) Depth: 5.56in (141.2mm) Height : 7.98in (202.8mm)	
	Unit Weight	1.84lbs (0.835kg)		
	Desktop Footprint	31.67in² (205cm²)		
Packaging Dimensions				
	Packaging Style	Bulk Package (K34009NA/EU) Retail Package (K34009US/AP/JP)		
	Packaging Dimensions	Width: 9.96in (253mm) Depth: 5.98in (152mm) Height: 3.58in (91mm)		
	Packaging Weight	3.84lbs (1.743kg)		
	Packaging Content	SD5600T Dock, TB3 cable, Dock Stand, Power Supply, IG (Instruction Guide), Warranty Card, Compliance Sheet, Welcome card insert for NA/EU SKU		
	Master Carton	4pcs		
Power and Environmer	tal			
	Power Adapter Rating	Input: 100-240V; 1.8A /	Input: 100-240V; 1.8A / Output: 20V DC 8.5A (170W)	
	Relative Humidity	55% operating temperature @ 77°F (25°C)		
	Operating Temperature	32 to 104°F (0 to 40°C)		
	Storage Temperature	-0.4 to 140°F (-18 to 60°	C)	
Country of Origin, Regu	llatory, and Warranty			
	Country of Origin	Thailand		
	Certification & Compliance	FCC, IC, CE, RCM, VCCI, C	B, RoHS, ACCO RSL	
	Warranty	3-Year Limited – Worldw	vide	



