

## SmartSockets® Table Top Surge Protector with USB

### AC OUTLET

- **6 AC Outlet with different color codes**
- **Suitable for 2-pole, 3-pole devices**
- 16ft wire exposed, Right Angle Plug
- 14AWG/3C, SJT, 2-in-1 Power Switch

### SURGE/ NOISE SUPPRESSION

- **AC Suppression Joule Rating:** 1500 Joules
- **Clamping Voltage:** 500V
- **Protection Modes:** Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression

### AC POWER RATING

- **AC Power:**
  - Input Voltage: 125V AC
  - Max Load: Up to 15A
  - Frequency Compatibility: 60Hz
  - Output (Watts): 1875

### USB CHARGING

- **USB Charger:**
  - Input Voltage: 90-125VAC@60Hz
  - Output Voltage: 5V ± 5%
  - Output Current: 4 Ports; Up to 5V/ 4.8A shared (24W)
  - Each Port can charge up to 5V/2.4A (12W)
  - Efficiency: ≥ 84% @25%, 50%, 75% and 100% load average
  - No Load Power Consumption: ≤0.1W @115Vac
  - Energy efficiency level V6
  - Smart IC (for Apple Charging, Samsung Charging, USB Battery Charging V1.2)

### PROTECTION

- **Short Circuit Protection**
- **Over Voltage Protection**
- **Over Power Protection**
- **Over Load Protection:** ≤ 2.9A per port, total shared ≤ 5.4A
- **Over Temperature Protection**
- **V0 Rating fire resistant housing**

All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets. Brand and product names mentioned are trademarks of their respective companies.

## LED INDICATOR

- **Two LED indicator lights let you know whether your equipment is protected.**

SmartSockets Surge	Grounded	Protection	Status
Off	Off	Off	Unit is not powered on
On	On	On	Your SmartSockets is plugged into an outlet that's properly grounded and is actively protecting your equipment.
On	Off	On	The situation is not immediately dangerous. However, you should contact your property manager or a qualified electrician to resolve the problem.
On	On or Off	Off	The surge protector has sustained damage. Disconnect your protector and send it to Kensington.

## PRODUCT DIMENSIONS

- **Unit Dimensions:**
  - Width: 184mm (7.24 in)
  - Length: 184mm (7.24 in)
  - Height: 44mm (1.73 in)
- **Unit Weight:** 1135g (2.50 lbs)
- **Enclosure Color and Material:** Black Plastic (ABS), PVC Power Cable

## PACKAGING DIMENSIONS

- **Packaging Style:** Retail Box
- **Packaging Dimensions:**
  - Width: 230mm (9.06 in)
  - Length: 50mm (1.97 in)
  - Height with Hangtag: 316mm (12.44 in)
  - Height without Hangtag: 284mm (11.18 in)
- **Packaging Weight:** 1600g (3.53lbs)
- **Package Content:**
  - Kensington K64494 Table Top Surge
  - Quick Start Guide
  - Warranty Information
  - Compliance Statement
  - SmartSocket Color Tag Labels
- **Master Carton:** 5 pcs

## ENVIRONMENTAL

- **Operating Temperature:** 0 to 40° C (32 to 104° F)
- **Storage Temperature:** -30 to 55° C (-22 to 131° F)
- **Relative Humidity:** 10% to 80% non-condensing

## COUNTRY OF ORIGIN, REGULATORY, AND WARRANTY

- **Country of Origin:** China
- **Warranty:** 1 Year Limited Warranty
- **Connected Equipment Insurance:** \$50,000
- **Certifications and Compliance:**
  - EMC: FCC Part 15, ICES-003
  - Safety: UL Certified (UL1449, UL1363, UL498, UL1310, UL1283)
  - Energy Efficiency (AC → DC): DOE Level 6 & NRCAN

All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets. Brand and product names mentioned are trademarks of their respective companies.