

SD4790P USB-C[®] and USB-A 10Gbps Quad 4K Hybrid Dock

Part Number: K33610NA | UPC Code: 0 85896 33610 5

Quad 4K for Windows or Chrome laptops and Triple 4K for MacBook M1/M2/M3. Ideal for professionals seeking a single docking solution that can support up to four external Ultra HD monitors, while also catering to mixed technology environments, the SD4790P USB-C[®] and USB-A 10Gbps Quad 4K Hybrid Dock supports the latest USB-C[®] and legacy USB-A^{*} laptops with video, data, and power—including triple monitor support for MacBook M1/M2/M3 laptops.

Providing a remarkable video experience with support for up to Quad 4K @ 60Hz, plug-and-play support for dual displays, and the ability to select between HDMI® and DP++ connections (6 video ports for up to 4 external displays), the SD4790P USB-C® and USB-A 10Gbps Quad 4K Hybrid Dock offers flexible display options without the need for adapters or dongles.

Supporting up to 10Gbps data transfer speeds via 6 USB ports and up to 100W of Power Delivery, the SD4790P USB-C[®] and USB-A 10Gbps Quad 4K Hybrid Dock satisfies the video, data, and power needs of most workstation setups.

*USB-A devices require optional power splitter (K38310WW) for Power Delivery.

Features include:

- Quad 4K Video via HDMI® and DP++
- Supports USB-C[®] and USB-A devices
- Windows, macOS, and Chrome OS
- Up to 100W Power Delivery
- Up to 10Gbps via 2 USB-C[®] ports and 4 USB-A ports
- Supports Zero-Footprint Mounting
- Kensington Security Cable Lock Slots
- 3-year limited warranty and Kensington DockWorks™ Software
- Sustainable components

SD4790P USB-C[®] and USB-A 10Gbps Quad 4K Hybrid Dock

Part Number: K33610NA | UPC Code: 0 85896 33610 5

Front

 DC 20V
 USB Host Port Up to 100W
 1 x DP 1.4 ++ 2 x DP 1.2 ++ 3 x HDM 12.0
 Ethernet 10/100/1000Mbps
 4 x USB-A 3.2 Gen1 5Gbps 5V/0.9A

SD4790P USB-C[®] and USB-A 10Gbps Quad 4K Hybrid Dock

Part Number: K33610NA | UPC Code: 0 85896 33610 5



Quad 4K Video via HDMI® and DP++

Enhance visual productivity and experience the versatility of plug-and-play for dual displays via USB-C® Alt mode or expand to Quad 4K @ 60Hz via two DisplayLink® connections. Six video ports allow you to select between HDMI® 2.0, DP++ 1.4, and DP++ 1.2 without the need for cumbersome adapters. Also supports M1/M2/M3 MacBook with triple displays.



Up to 100W Power Delivery

Delivers power to laptop, docking station, and connected accessories. Supports up to 100W for USB-C® Alt Mode laptops and continues to charge connected accessories even when host laptop is not connected. Optional 100W Power Splitter (K38310WW) needed to supply power for USB-A laptops.



6 USB Ports, Gigabit Ethernet, and Combo Audio Jack

Delivers speeds up to 10Gbps via 2 USB-C[®] ports and 4 USB-A ports. Front: 2 x USB-C 3.2 Gen2 10Gbps (one 5V/1.5A and one 5V/0.9A). Back: 4 x USB-A 3.2 Gen1 5Gbps (5V/0.9A). Includes 1Gbps Ethernet port and combo audio jack.



Zero-Footprint Mounting Option and Security Cable Lock Slots

Maximize desktop space by mounting your docking station out of the way. Mounting bracket sold separately (K34050WW). Protect your investment with a Kensington cable lock (K65020WW or K65021WW), sold separately.



Universal Compatibility

Supports Thunderbolt™ 4, USB4®, USB-C®, and legacy USB-A laptops running Windows 10 or above, macOS 11 or above, Chrome OS 114 or above.



Secure Screw Lock Connection

Host cable is equipped with secure screw lock connector for a consistent and reliable connection between the docking station and the laptop.



Free Kensington DockWorks™ Software and 3-Year Limited Warranty

Free DockWorks[™] software delivers the best connection, performance, and security from your Kensington dock. Enjoy peace of mind knowing your covered by Kensington with a professional warranty. card readers.



Sustainability Focused

Composed of 73% postconsumer recycled content (PCR), the plastic material used in the SD4790P docking station is aimed at reducing our environmental impact.

Product Sheet

SD4790P USB-C[®] and USB-A 10Gbps Quad 4K Hybrid Dock

Part Number: K33610NA | UPC Code: 0 85896 33610 5

System Requirements

	Systems Supported	All laptops with DisplayLink software
	Operating Systems Supported	Windows [®] 10 or above macOS 11 or above
		Chrome OS 114 or above
	Plug & Play	Video 1 and Video 2 ports support plug-and-play, while Video 3 and Video 4 ports require the installation of the DisplayLink® driver. *All Chromebooks using ChromeOS build R114 or later will work with DisplayLink docks and adapters without additional driver installation *Windows 10 S products using DisplayLink technology will get their device drivers either from OEM pre-installation or from Windows Update
	Software	Download from DisplayLink website (https://www.displaylink.com/downloads)
	System Resource Requirement	CPU: Intel® Core™ i5 6th generation or above Memory: 8Gb or above GPU: Intel® HD Graphics 620 or above
	Additional Software Information	DockWorks compatible (Windows [®] 10 or above)
	USB-C Power Delivery	PD3.0: 5V, 9V, 15V/3A & 20V/5A (up to 100W)
USB Interface		
	Type of USB Connector	USB-C Screw Lock Connector with USB-A adapter
	Host Connector	Supports Thunderbolt™ 4 / Thunderbolt™ 3 / USB4 / USB-C®/ USB-A
USB Connections		
	Ports	Front Panel : - 1 x USB-C 3.2 Gen2 10Gbps (5V/1.5A, supports BC 1.2*) * USB Battery Charging 1.2-compliant devices - 1 x USB-C 3.2 Gen2 10Gbps (5V/0.9A) - 1 x 3.5mm Audio Combo Jack
		Back Panel : - 1 x DP 1.4 ++ - 2 x DP 1.2 ++ - 3 x HDMI 2.0 - 4 x USB-A 3.2 Gen1 5Gbps (5V/0.9A) - 1 x Ethernet Port 10/100/1000Mbps - 1 x DC Input - 1 x USB Host Port (Up to 100W charging)
		Side Panel: - 1 x Power Button

SD4790P USB-C[®] and USB-A 10Gbps Quad 4K Hybrid Dock

Part Number: K33610NA | UPC Code: 0 85896 33610 5

Network Connections

	Ethernet Port	RJ45
	Compatible Ethernet Speeds	10/100/1000 Mbps
Host Connectivity		
	Host Docking Connector	Connecting with USB-C: Full function video/USB ports, Power Delivery up to 100W Connecting with USB-A: Only output video through DisplayLink ports, full function with USB ports, additional power input is necessary

Video Connections

High	n Ender Dilution Ender	ŢŢ	▣▣▣	
Thunderbolt™ 3** / Thunderbolt™ 4** / USB4®** / USB-C® Alt Mode with DP1.4++ HBR3 (Windows) (DSC on)	Up to 4K @ 60Hz*	Up to 4K @ 60Hz*	Up to 4K @ 60Hz*	Up to 4K @ 60Hz*
MacBook M1/M2/M3 Pro or Max	Up to 4K @ 60Hz*	Up to 4K @ 60Hz*	Up to 4K @ 60Hz*	х
USB-C [®] (DP1.2++) or USB-A devices do not support Alt Mode.	Up to 4K @ 60Hz*	Up to 4K @ 60Hz*	х	х
Thunderbolt™ 3** / Thunderbolt™ 4** / USB4®** / USB-C® Alt Mode with DP1.4++	esh Rate	HZ HZ 1080P@240Hz	Hz Hz Hz	Hz Hz Hz X
HBR3 (Windows)	Video Connectors	2 x D	visplayPort ++ v1.4 visplayPort ++ v1.2 IDMI 2.0	
	Maximum Resolution Supp	Dual Triple	le Monitor: Up to 4K @ 6 Monitors: Up to 4K @ 6 e Monitor: Up to 4K @ 6 druple Monitors: Up to 4 Ied	0Hz with DSC enabled 0Hz with DSC enabled

*Support for Display Stream Compression (DSC) is based on the capabilities of the host device and monitor.

**This USB-C[®] Dock will be compatible with Thunderbolt™ 3, Thunderbolt™ 4, and USB4[®] laptops, however, at a bandwidth of up to 10Gbps.

SD4790P USB-C[®] and USB-A 10Gbps Quad 4K Hybrid Dock

Part Number: K33610NA | UPC Code: 0 85896 33610 5

Audio Connections		
	Audio Connectors	1 x 3.5mm audio combo jack
	Audio Channels Supported	Stereo LR
LED Indicator		
	Blue LED	Power indicator
Material Specifications		
	Exterior	Enclosure: PC ABS with texture. The plastic material utilized in this docking station is composed of 73% post-consumer recycled conten (PCR).
	Product Color	Black
Other Features		
	Kensington Security Slot	Kensington Security Slot Kensington Nano Security Slot
Product Dimensions		
	Cable Dimensions	39.4 in (1m)
	Unit Weight	1.01lbs (0.46kg)
	Unit Dimensions without Peripherals	7.87 x 3.35 x 1.18 in (200 x 85 x 30 mm)
	Desktop Footprint	26.35in² (170cm²)
Packaging Dimensions		
	Packaging Style	Retail Package (K33610NA)
	Packaging Dimensions	8.54 x 4.25 x 4.02 in (217 x 108 x 102 mm)
	Packaging Weight	2.6 lbs (1.18 kg)
	Packaging Content	 1 x SD4790P USB-C & USB-A Quad 4K Docking Station Hybrid Docking Station 1 x USB-C 3.2 Gen2 Cable with USB-A Adapter and Screw Lock 1 x 150W Power Supply Unit 1 x Power Cord 1 x Quick Installation Guide 1 x Compliance Sheet 1 x Warranty Card 1 x Welcome Card
	Master Carton	6

SD4790P USB-C[®] and USB-A 10Gbps Quad 4K Hybrid Dock

Part Number: K33610NA | UPC Code: 0 85896 33610 5

Power & Environmental

	Power Adapter Rating	Input: 100-240V; 2.5A Output: 20V DC 7.5A (150W)
	Relative Humidity	55% operating temperature @ 77° F (25°C)
	Operating Temperature	32 to 113°F (0 to 45°C)
	Storage Temperature	14 to 149°F (-10 to 65°C)
Country Of Origin, Re	egulatory, and Warranty	
	Country of Origin	Thailand

Country of OriginThailandCertifications & ComplianceFCC, IC, CE, CB, ErP, RoHs, ACCO RSL, UKCA, VCCI, RCMWarranty3-Year Limited - Worldwide



All specifications are subject to change without notice. Products may not be available in all markets. Kensington® and Kensington, The Professionals' Choice™ are trademarks of ACCO Brands. All other registered and unregistered trademarks are the property of their respective owners. © 2023 Kensington Computer Products Group, a division of ACCO Brands. k23-20172p

