

SD4785P USB-C & USB-A 10Gbps Dual 4K Hybrid Docking Station w/ 100W PD - DP++ & HDMI (DFS)

Part Number: K33640NA | UPC Code: 0 85896 33640 2

The ultimate
Surface hybrid
docking solution
for Dual 4K@60Hz
video, with 100W
power delivery.


Designed for Surface, the SD4785P USB-C & USB-A 10Gbps Dual 4K Hybrid Docking Station w/ 100W PD - DP++ & HDMI (DFS) is the ultimate hybrid docking solution for Ultra High Definition Dual 4K @ 60Hz video. Features include the ability to select between HDMI 2.0 and DP++ 1.2, with four video ports in all (no need for cumbersome adapters); six USB ports; 100W of power delivery; a 1m (3.28 feet) USB-C to USB-C cable with USB-A adapter; Thunderbolt 3 compatibility; optional Kensington DockWorks™ software, for the best connection, performance, and security from your Kensington dock; and a three-year warranty. VESA compatible.

Features include:

- Designed for Surface
- Ultra High Definition video for up to two 4K monitors @ 60Hz
- 10Gbps throughput for maximum efficiency
- Flexibility to select between HDMI 2.0 and DP++ 1.2 ports

 choose the best port for your environment
- Up to 100W of power delivery (PD 3.0)
- Six USB ports (two with charging)
- 1m (3.28 feet) USB-C to USB-C cable with USB-A adapter included
- Free DockWorks™ software
- Three-year warranty







SD4785P USB-C & USB-A 10Gbps Dual 4K Hybrid Docking Station w/ 100W PD - DP++ & HDMI (DFS)

Part Number: K33640NA | UPC Code: 0 85896 33640 2







Designed for Surface

Kensington worked directly with Microsoft to provide professional-level connectivity that looks as good as it functions, so you can work like a pro. Connect with confidence for a seamless dock and charge experience.

Dual 4K Video Output (HDMI 2.0 and DP++ 1.2 @ 60Hz)

Delivers Ultra High Definition (4096 x 2160) images. Four video ports allow users the ability to select between HDMI 2.0 and DP++ 1.2 without the need for cumbersome adapters.

Up to 100W Power Delivery (PD 3.0)

For fast charging.



Six USB Ports (USB-A and USB-C)

Two-layer hub delivers speeds up to 10Gbps.
Front: 1x USB-C 3.2 Gen2 up to 5V/3A and 1x USB-A 3.2 Gen2 up to 5V/2.4A;
Back: 4x USB-A 3.2 Gen1 up to 5V/0.9A



Free Kensington DockWorks™ Software

Enables the best connection, performance, and security from your Kensington dock.



Three-Year Warranty

Rest assured knowing you're covered by Kensington.



Zero Footprint Mounting Option

Adjustable clamp easily attaches to a desktop edge, cubicle wall, monitor arm, or other surface for maximum mounting flexibility (K34050, sold separately).

SD4785P USB-C & USB-A 10Gbps Dual 4K Hybrid Docking Station w/ 100W PD - DP++ & HDMI (DFS)

Part Number: K33640NA | UPC Code: 0 85896 33640 2

	Systems Supported	USB-C or USB-A Laptops & Ultrabooks and Monitors that support up to 4K	
	Operating Systems Supported	Windows® 7 or above	
	Plug & Play	DisplayLink Driver needed	
	Software	Download from DisplayLink website (https://www.displaylink.com/downloads)	
	System Resource Requirement	CPU: Intel® Core™ i5 6th generation or above Memory: 8GB or above GPU: Intel® HD Graphics 620 or above	
	Additional Software Information	DockWorks (Windows 7 or above)	
	USB-C Power Delivery	5V/ 9V/ 12V/ 15V/ 20V @ 3A (up to 100W, 20V@5A	
USB Interface			
	Type of USB Connector	USB-C & USB-A Connector	
	Host Connector	Support USB-C 3.2 Gen2 & USB-A 3.2 Gen2	
USB Connections			
	Ports (Front)	1 x USB-A 3.2 Gen2, support BC1.2 (5V/1.5A) & Apple Charging (5V/2.4A) 1 x USB-C 3.2 Gen2 (5V/3A, 9V/2A)	
	Ports (Back)	4 x USB-A 3.2 Gen1 (5V/0.9A)	
Network Connections			
	Ethernet Port	RJ45	
	Compatible Ethernet Speeds	10/100/1000 Mbps	
Host Connectivity			
	Host Docking Connector	USB-C host device must support Power Delivery. Power Delivery is not supported on USB-A host devices without the use of the optional 60W power splitter (K38310)	
Video Connections			
	Video Connectors	2 x DisplayPort ++ v1.2 2 x HDMI v2.0	
	Maximum Resolution Supported	Single Monitor: 4096 x 2160 @ 60Hz Dual Monitors: 4096 x 2160 @ 60Hz	
Audio Connections			
	Audio Connectors	1 x 3.5mm audio combo jack	
	Audio Channels Supported	Stereo LR	

SD4785P USB-C & USB-A 10Gbps Dual 4K Hybrid Docking Station w/ 100W PD - DP++ & HDMI (DFS)

Part Number: K33640NA | UPC Code: 0 85896 33640 2

	Blue LED	Power indicator
	Dide LLD	Tower maleator
Material Specifications		
	Exterior	Enclosure: PC ABS with texture
	Bottom	Metal Base Plate: Sheetmetal
	Product Color	PMS Black
Other Features		
	Kensington Security Slot	Kensington Security Slot / Nano Slot
	VESA Mount Compatible	Yes
Product Dimensions		
	Unit Weight	13.58oz (0.385kg)
	Unit Dimensions without Peripherals	Width: 8.26in (210mm) Depth: 3.54in (90mm) Height: 1.23in (31.3mm)
	Enclosure Color & Material	PMS Black, PC ABS
	Desktop Footprint	29.29in² (189cm²)
Packaging Dimensions		
	Packaging Style	Brown Box (K33640NA)
	Packaging Dimensions	Width: 9.25in (235mm) Depth: 5.86in (149mm) Height: 3.58in (91mm)
	Packaging Weight	3.07lbs (1.396kg)
	Packaging Content	1 x SD4785P Dock 1 x USB-C to USB-C cable with USB-A tether 1 x Power Supply 1 x IG (Instruction Guide) 1 x Warranty Card 1 x Compliance Sheet 1 x Welcome card insert for NA SKU
	Master Carton	4

SD4785P USB-C & USB-A 10Gbps Dual 4K Hybrid Docking Station w/ 100W PD - DP++ & HDMI (DFS)

Part Number: K33640NA | UPC Code: 0 85896 33640 2

Power	and	Environmental

	Devide compatible with	Surface Go 4, Surface Go 3, Surface Go 2, Surface Go Surface Laptop Studio 2, Surface Laptop Studio, Surface Laptop Go 3, Surface Laptop Go 2, Surface Laptop Go
Compatibility		
	Warranty	3-Year Limited - worldwide
	Certifications & Compliance	FCC, IC, CE, RCM, VCCI, CB, RoHS, ACCO RSL
	Country of Origin	Thailand
Country of Origin,	Regulatory, and Warranty	
	Storage Temperature	-0.4 to 140°F (-18 to 60°C)
	Operating Temperature	32 to 104°F (0 to 40°C)
	Relative Humidity	55% operating temperature @ 25°C
	Power Adapter Rating	Input: 100-240V; 1.8A / Output: 20V DC 8.5A (170W



