

Simple Solutions™ Wired Keyboard (TAA)

Part Number: K55113US | UPC Code: 085896551133

The perfectly simple plugand-play keyboard.



The Simple Solutions™ Wired Keyboard (TAA) is the perfectly simple plug-and-play keyboard. Features include a quiet-clicking full-size keyboard (104 keys) that offers smooth, non-disruptive operation, with 10 multimedia keys and a numeric keypad; TAA-compliance, making it ready for use in U.S. Federal Government institutions and organizations; Windows, macOS, and Chrome OS compatibility; and a three-year warranty, so you can rest assured knowing you're covered by Kensington.

Features include:

- · Reliable plug-and-play operation
- · Wired USB-A 2.0 connection
- Full size keyboard (104 keys) with 10 multimedia keys
- · Quiet clicking
- Compatible with Windows, macOS, and Chrome OS
- TAA-Compliant
- · Three-year warranty







Kensington

Simple Solutions™ Wired Keyboard (TAA)

Part Number: K55113US | UPC Code: 085896551133



Reliable Plug-and-Play Operation Wired USB-A connection delivers reliable performance without the need for batteries. Compatible with Windows, macOS, and Chrome OS.



Full-Size Keyboard
Six row, 104-key layout with numeric keypad.



Quiet ClickingFor smooth, non-disruptive operation.



TAA-Compliant
Ready for use in U.S. Federal
Government institutions and
organizations.



Three-Year Warranty Rest assured knowing you're covered by Kensington.



Simple Solutions™ Wired Keyboard (TAA)

Part Number: K55113US | UPC Code: 085896551133

System	Req	uirement

	Port	1x Type A USB Port
	Operating Systems Supported	Windows, macOS, iOS & Chrome OS
Product Dimensions		
	Unit Dimensions	Width: 17.32in (440mm) Length: 5.78in (147mm) Height: 1.85in (47mm)
	Unit Weight	0.37lbs (560g)
	Color	Black
Packaging Dimensions		
	Packaging Style	B2B Box
	Packaging(Unit)	Width: 7.08in (180mm) Length: 18.11in (460mm) Height: 1.57in (40mm)
	Packaging Weight(Unit)	1.52lbs (0.69kg)
	Master Carton	5 pcs
	Package Content	Keyboard, Instruction Guide, Warranty Card 8 Compliance Sheet
Power & Environmental		
	Battery	None
	Operating Temperature	0 to 45°C (32 to 113°F)
	Storage Temperature	-15 to 60°C (5 to 140°F)
	Relative Humidity	0% to 90% non-condensing
Country of Origin, Regulatory, &	ι Warranty	
	Country of Origin	Taiwan
	Certifications and Compliance	FCC
	Warranty	3-Year Worldwide



