

MD125U4 USB4 Portable Docking Station (DFS)

Part Number: K32857WW | UPC Code: 0 85896 32857 5

A powerful and portable USB4 dock for your Surface.



Designed exclusively for Surface, the innovative MD125U4 USB4 Portable Docking Station seizes the power of USB4 technology to maximize productivity, reduce travel bulk, and help you get the most from your Surface—while at your desk or on the go.

With all the power of USB4, including Dual 4K support, up to 40Gbps upstream speed, and up to 100W power pass-through, the MD125U4 maximizes your productivity anywhere.

An ideal choice for hybrid workers who want to travel with less weight and clutter, power pass-through eliminates the need to travel with an additional power brick, and a variety of productivity ports eliminates the need for additional adapters.

At your desk or on the go, the MD125U4 is the perfect mobile dock for your Surface.

Features include:

- Built in collaboration with Microsoft to utilize USB4 technology for Surface
- Supports USB4, Thunderbolt 3, •
 Thunderbolt 4, and USB-C 3.2
 devices
- Two HDMI 2.1 ports deliver up to 4K @ 120Hz for dual monitors
- Powered by a USB-C power adapter—or the Surface battery when traveling
- One USB-C 3.2 Gen2 port, two USB-A 3.2 Gen2 ports, and one 2.5Gbps Ethernet port
- Easily fits into your backpack for productivity on the go
- Soft fabric design complements your workspace

Kensington

MD125U4 USB4 Portable Docking Station (DFS)

Part Number: K32857WW | UPC Code: 0 85896 32857 5





Kensington

MD125U4 USB4 Portable Docking Station (DFS)

Part Number: K32857WW | UPC Code: 0 85896 32857 5









Designed Exclusively for Surface

Kensington worked directly with Microsoft to provide professional-level connectivity that looks as good as it functions. Connect with confidence for a seamless dock and charge experience.

Universal Compatibility

Leading the way with USB4 connection technology, the MD125U4 supports USB4, Thunderbolt 3, Thunderbolt 4, and USB-C 3.2 devices running Windows 10 or above.

Maximizes Video Output

Two HDMI 2.1 ports deliver up to 8K @ 30Hz for a single monitor, and up to 4K @ 120Hz for dual monitors so you can extend your visual productivity with the resolution, contrast, and color depth of Ultra HD.

Up to 100W Power Pass-Through

Plug your USB-C power adapter (80W or greater) into the dock for pass-through power to the device, or power the dock and connected devices using the Surface's battery when traveling. Add the optional 100W Power Adapter (sold separately) for video, data, and power all in one dock.



Productivity Ports

Extend productivity with up to 40Gbps upstream speed. Includes one USB-C 3.2 Gen2 port supporting data transfer and power pass-through (5V/0.9A charging via Bus power, up to 100W charging via power pass-through), two USB-A 3.2 Gen2 ports, and one 2.5Gbps Ethernet port.



Sleek, Compact Design

Fits into your backpack or carrying case for productivity on the go. Matte, soft-touch coating, and soft fabric surface add protection while visually complementing your workspace.



Cable Storage Clips

Neatly stow the 9.8" (25cm) USB4 cable during transport and when not in use.



3-Year Limited Warranty

A 3-year limited warranty lets you rest assured knowing you're covered by Kensington.

Kensington

MD125U4 USB4 Portable Docking Station (DFS)

Part Number: K32857WW | UPC Code: 0 85896 32857 5

| Sv | /stem | Rea | uirem | ents |
|----|-------|-----|-------|------|
| | | | | |

| | Systems Supported | All Laptops with either Thunderbolt 3/4 or USB-C/USB4 ports |
|---------------------|------------------------------|--|
| | Operating Systems Supported | Windows 10 or above |
| | Plug & Play | Yes |
| | System Resource Requirement | CPU: Intel® Core™ i5 6th generation or above Memory: 8Gb or above GPU: Intel® HD Graphics 620 or above |
| | USB-C Power Delivery | PD3.0, 5V/ 9V/ 15V/ 20V@5A (up to 100W) Power pass-through up to 100W |
| USB Interface | | |
| | Type of USB Connector | USB-C Connector |
| | Host Connector | Supports USB4, USB3.2 Gen2/Gen1 Type-C with USB-C Alt Mode and Power Delivery |
| USB Connections | | |
| | Ports | Front Panel: - 2 x HDMI 2.1 - 1 x 2.5Gbps Ethernet Rear Panel: - 1 x USB-C Upstream Cable Side Panel: - 1 x USB-C 3.2 Gen2 10Gbps (5V/0.9A, up to 100W power pass-through) - 2 x USB-A 3.2 Gen2 10Gbps (5V/0.9A) |
| Network Connections | | |
| | Ethernet Port | RJ45 |
| | Compatible Ethernet Speeds | 10/100/1000/2500 Mbps |
| Video Connections | | |
| | Video Connectors | 2 x HDMI 2.1 |
| | Maximum Resolution Supported | Dual Display is up to 2 x 4K@120Hz* Single Display is up to 1 x 8K@30Hz* * Host is HBR3 (DSC on) |

| HOST | Single 🖵 | Dual 🖵 🖵 | Single/Refresh | Dual/Refresh |
|------------------------|-----------|----------|----------------|--------------|
| Surface Pro 9 - Intel® | 8K@30Hz** | 4K@60Hz | 4K@120Hz | 4K@120Hz |
| Surface Pro 9 - ARM | 4K@60Hz | 4K@60Hz | 4K@60Hz | 2K@120Hz |
| Surface Pro 8 | 4K@60Hz | 4K@30Hz | 4K@60Hz | 2K@120Hz |
| Surface Laptop 5 | 8K@30Hz** | 4K@60Hz | 4K@120Hz | 4K@120Hz |
| Surface Laptop 4 | 4K@30Hz | FHD@60Hz | | |
| Surface Laptop Studio | 4K@120Hz | 4K@30Hz | 4K@120Hz | 2K@120Hz |
| Surface Pro X | 4K@30Hz | 2K@60Hz | | |
| Surface Laptop Go | 4K@30Hz | FHD@60Hz | | |
| Surface Go 3 | 4K@30Hz | FHD@60Hz | | |

^{**}Support for Display Stream Compression (DSC) is based on the host device and monitor capabilities.



MD125U4 USB4 Portable Docking Station (DFS)

Part Number: K32857WW | UPC Code: 0 85896 32857 5

| Host Connectivity | |
|-------------------|-----------|
| | Host Dock |

| Host Connectivity | | |
|-------------------------|-------------------------------------|--|
| | Host Docking Connector | USB-C with up to 100W Power Pass-Through (USB4 with up to 40Gbps upstream speeds - video 30Gbps, USB 10Gbps) |
| Material Specifications | 5 | |
| | Exterior | PC + ABS with texture, top fabric wrapped dock cover |
| | Interior | Sheet metal (steel) |
| | Bottom | PC + ABS with texture |
| | Product Color | Pantone Black C |
| Product Dimensions | | |
| | Unit Weight | 0.42lbs (0.19kg) |
| | Unit Dimensions without Peripherals | 3.98 x 3.98 x 0.9in (101 x 101 X 22.9mm) |
| | Enclosure Color & Material | PC + ABS with texture, Pantone Black C, Top fabric wrapped dock cover |
| | Desktop Footprint | 15.84in² (102.01cm²) |
| Packaging Dimensions | | |
| | Packaging Style | Retail Package |
| | Packaging Dimensions | 7.89 x 4.82 x 1.59in (201 x 123 x 41mm) |
| | Packaging Weight | 0.95lbs (0.43kg) |
| | Packaging Content | 1 x MD125U4 1 x Instruction Guide 1 x Warranty Card 1 x Compliance Sheet |
| | Master Carton | 5pcs |
| Power & Environmenta | al | |
| | Relative Humidity | 55% operating temperature @ 77°F (25°C) |
| | Operating Temperature | 32 to 104°F (0 to 45°C) |
| | Storage Temperature | 32 to 140°F (0 to 60°C) |
| Country of Origin, Regu | ulatory, and Warranty | |
| | Country of Origin | Taiwan |
| | Certifications & Compliance | FCC, IC, CB, RoHS, ACCO RSL |
| | Warranty | 3-Year Limited - worldwide |



